

---

# **iqMAXREFDES42 Documentation**

***Release 1.1.1***

**IQ2 Development GmbH**

August 07, 2014



<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	Board Specification . . . . .	3
1.2	Project Goal . . . . .	4
<b>2</b>	<b>Sensor Logic</b>	<b>5</b>
<b>3</b>	<b>IO-Link Application</b>	<b>7</b>
3.1	Process Data In . . . . .	7
3.2	Process Data Out . . . . .	7
3.3	Commands . . . . .	7
3.4	Parameters . . . . .	8
3.5	Events . . . . .	8
<b>4</b>	<b>Installation Details</b>	<b>9</b>
4.1	Firmware . . . . .	9
4.2	Source Code . . . . .	9
<b>5</b>	<b>Troubleshooting</b>	<b>11</b>
<b>6</b>	<b>Changelog</b>	<b>13</b>
6.1	v1.1.1 (2014-07-28) . . . . .	13
6.2	v1.1 (2014-06-07) . . . . .	13
6.3	v1.0 (2014-05-17) . . . . .	13
<b>7</b>	<b>Glossary</b>	<b>15</b>
<b>8</b>	<b>License</b>	<b>17</b>



**Release** 1.1.1

**Date** August 07, 2014



---

## Introduction

---




Maxim's Mojave (MAXREFDES42#) reference design features a resistance to digital temperature sensor which can also detect multiple faults. The IO-Link communication protocol enables quick sensor configuration and reduces cabling while featuring a robust, medium speed, communication protocol with power, enabling higher powered sensors than a 4-20mA loop.

### 1.1 Board Specification

Item	Specification
Oscillator Frequency	18.432MHz
Microcontroller	Renesas RL78/G1A (R5F10E8EALA)
DC Power	24V via M12 Connector
LEDs	<ul style="list-style-type: none"><li>• Power indicator: Green x1</li><li>• IO-Link indicator: Amber x1</li><li>• Digital output indicator: Red x1</li></ul>
IO-link Connector	Male M12 4-pole A-coded
IO-Link PHY	Maxim MAX14821EWA+
RTD-to-Digital Converter	MAX31865ATP+
SPI 3.3V/5V Level Shifter	MAX1841EUB
Dot Addressable Display	SCE5744 Z

## 1.2 Project Goal




The purpose of this project is by giving the user a strong basis to start develop production-ready IO-Link® application based on Maxim Integrated IO-Link device transceiver (MAX14821), a Renesas ultra-low-power, 16-bit microcontroller (RL78) and iqStack® IO-Link Device Stack.



Sensor Logic

In iqMAXREFDES42 have been implemented simple switch-point hysteresis logic and additionally can be configured as normally open (NO) or normally closed (NC).



By default ambient temperature switch-point settings (32767 is the maximal value):

What	SP (Level)	Hysteresis	Mode
Ambient temperature	9148 (0x23BC, 30°C/86°F)	32 (0x20, 1°C/1.8°F)	Normally Open (NO)

**Note:** Ambient temperature switch-point flag always indicated on digital output channel (red LED).



### 3.1 Process Data In

### 3.2 Process Data Out

### 3.3 Commands

Value	Description
128 (0x80)	Device Reset
160 (0xA0)	Tech-in ambient temperature switch-point level (see IO-Link index 0x0100 below)

### 3.4 Parameters

IO-Link index	Mode	Description	Default value
16 (0x0010)	read-only	Vendor Name	Maxim Integrated
17 (0x0011)	read-only	Vendor Text	The world leader in analog integration
18 (0x0012)	read-only	Product Name	Mojave (MAXREFDES42#)
19 (0x0013)	read-only	Product ID	MAXREFDES42
20 (0x0014)	read-only	Product Text	IO-Link RTD Temp Sensor
23 (0x0017)	read-only	Firmware Revision	v 1.1.1
256 (0x0100)	read/write	Ambient temperature switch-point level	9148 (0x23BC, 30°C/86°F)
257 (0x0101)	read/write	Ambient temperature switch-point hysteresis	32 (0x20, 1°C/1.8°F)
258 (0x0102)	read/write	Display's temperature scale (0 - °F, 1 - °C)	1 (0x01)
259 (0x0103)	read/write	N-wire type connection (2, 3, 4)	2
260 (0x0104)	read/write	MAX31865ATP+ Configuration register	0xCO (2-wire or 4-wire auto conversion mode)
261 (0x0105)	read-only	MAX31865ATP+ RTD (2 bytes)	0
262 (0x0106)	read/write	MAX31865ATP+ High Fault Threshold (2 bytes)	0xFFFF
263 (0x0107)	read/write	MAX31865ATP+ Low Fault Threshold (2 bytes)	0
264 (0x0108)	read-only	MAX31865ATP+ Fault Status register	0x00

### 3.5 Events

Event code	Description
0x4210	Device temperature over-run
0x5000	Device hardware fault
0x5111	Primary supply voltage under-run
0x6000	Device software fault
0x7710	Short circuit

---

## Installation Details

---

There are two ways to experiment with MAXREFDES42#:

- Upload Firmware HEX-file, connect a device to IO-Link Master and play around.
- Clone the source code from Bitbucket repository, go throw and try to debug.

### 4.1 Firmware

Firmware HEX-file, IODDs data and this document in PDF format can be downloaded from the [Bitbucket repository](#) absolutely free without registration.

To upload HEX-file into MAXREFDES23 have to get [Renesas E1 emulator](#) and also [Renesas Flash Programmer](#).

### 4.2 Source Code

The project source code can be cloned from the [Bitbucket repository](#) freely without registration.

Download a trial version of [IAR RL78 Embedded Workbench IDE](#) in order to compile it and also take a look for [Renesas Application Leading Tool \(Applilet\)](#).

Also the [Renesas E1 emulator](#) and [Renesas Flash Programmer](#) needed to start debug session with a device.



---

## Troubleshooting

---

If during power-on self-test (POST) hardware fails were occurred, then the main sensor application will not started and instead a first appeared hardware fail number was blinked on digital output red-indicator channel continuously and also was displayed on LCD.

Blinks Count	Fail Description
1	Renesas RL78 Illegal memory access (a firmware error, contact with developers)
2	Renesas RL78 RAM parity check (a firmware error, contact with developers)
3	Renesas RL78 Illegal instruction (a firmware error, contact with developers)
4	Maxim MAX14821EWA+ selfcheck (the chip is possibly corrupt, try to restart the device)
5	Maxim MAX31865ATP+ selfcheck (the chip is possibly corrupt, try to restart the device)





---

## Changelog

---

### 6.1 v1.1.1 (2014-07-28)

- Improvements:
  - (#4) Callendar-Van Dusen equation

### 6.2 v1.1 (2014-06-07)

- **Breaking changes:**
  - (#3) MAX31865ATP+ RTD-to-Digital Converter registers are available as IO-Link parameters
  - (#6) Switch N-wire connection type via an IO-Link parameter
- Improvements:
  - (#5) IODD picture and icon was added

### 6.3 v1.0 (2014-05-17)

- New features:
  - Hardware setups:
    - \* Renesas RL78/G1A (R5F10E8EALA) microcontroller (with Applilet3 support, see 'src\applilet3\_src')
    - \* MAX14821EWA+ IO-Link Device Transceiver (SPI/UART, see 'src\hw\_drivers\c\_max1482x.\*')
    - \* MAX31865ATP+ RTD-to-Digital Converter (SPI, see 'src\hw\_drivers\c\_max31865.\*')
    - \* SCE574x 4-Character 5x7 Dot Matrix Serial Input Dot Addressable Display (SPI, see 'src\hw\_drivers\c\_sce574x.\*')
  - Porting IO-Link iqStack(R) Device and set up the IO-Link communication (see 'src\applilet3\_src\r\_main.c')
  - Write a simple IO-Link *resistor temperature detector* Application (with appropriate IODDs, see 'src\sensor\_appl.c')



---

## Glossary

---

**RTD** Short for *resistor temperature detector*.

**PV** Short for *process value*.

**resistor temperature detector** Temperature sensor that operates on the measurement principle that a material's electrical resistance changes with temperature.

**process value** Internal unsigned numeric number, must be converted in order to display a required physical value.



---

### License

---

All source files with the correspondent header notes are the subject to the IQ<sup>2</sup> Development GmbH terms and conditions defined in file `Allgemeine Vertragsbedingungen.pdf`.

For any other details please [contact with us](#).